



RAMP AND TSGI NOTES

1. RAMP SURFACE TO BE ROUGHENED FOR TRACTION (DEEP BROOM FINISH) OR TREATED WITH NON-SLIP MATERIAL.
2. RAMP TO BE ALIGNED IN THE DIRECTION OF TRAVEL.
3. PROVIDE DISTINCT CHANGE OF GRADE (ie. NO ROUNDING) BETWEEN THE RAMP SURFACE AND THE LANDING AND BETWEEN THE RAMP SURFACE AND WING. ALL RAMP GRADES TO BE IN ACCORDANCE WITH AS 1428.1
4. TACTILE INDICATOR TILES TO BE MANUFACTURED AND INSTALLED TO AUSTRALIAN STANDARD AS 1428.4
5. ENSURE THE RAMP AND GUTTER ARE FORMED INTEGRALLY.
6. FOR TSGI INSTALLED IN EXISTING PAVEMENT, CONTRACTOR SHALL SAWCUT EXISTING PAVEMENT AND INSTALL TSGI TILES ON MORTAR BED AND ENSURE FLUSH WITH SURROUNDING SURFACE LEVELS.

NOTE:
HOLDING RAILS TO BE CAST INTO CONCRETE PLINTH AT RAMPS.
FOOTINGS REQUIRED WHERE RAILS INSTALLED INTO MEDIAN BREAKS



ALICE SPRINGS TOWN COUNCIL
CNR TODD STREET AND GREGORY TERRACE
PHONE: (08) 89 500 500
FAX: (08) 89 530 558

SUBDIVISION AND DEVELOPMENT GUIDELINES			
STANDARD KERB RAMP			
REV C	DESCRIPTION DESIGN ISSUE	DATE 05.02.18	INITIALS ASTC

DRAWING NUMBER: ASTC - 112	AMENDMENT: C
DESIGNED: MP	SCALE: NOT TO SCALE
SURVEYED: N/A	DATE: FEB 2018
DRAWN: MR/TJK	